BUILDING PRODUCT INFORMATION — BPIR:CHIIBA-COM:2026.V1

Chief 125 aluminium internal spouting bracket

Component BPIR. Supersedes BPIR:CHIIBA-COM:2023.v1. Issued under the Building (Building Product Information Requirements) Regulations 2022.

Product and manufacturer details

Product name	Chief 125 aluminium internal spouting bracket
Product identifier	CHIIBA-COM
Manufacturer's name & address	Continuous Group Ltd, 6 Yashili Drive, Pokeno 2402
Manufacturer's email address	cg@continuous.co.nz
Manufacturer's web address	www.continuous.co.nz
Manufacturer's NZBN	9429034817001
Place of manufacture	Aotearoa New Zealand
Warnings & bans	No

Product description

Chief 125 aluminium internal spouting bracket is a spouting bracket used in the installation of Chief 125 spouting system.

TABLE 1 — MATERIALS

COMPONENT	COMPONENT MATERIAL
CG Chief 125 internal bracket	2.00mm BMT aluminium, grade 5052-H32

Installation requirements

Refer to Chief 125 pre-painted metal spouting system BPIR:CHIPM-SYS:2023.v2 for full system and installation details.

Scope of use

Chief 125 aluminium internal spouting bracket is designed to fit Chief 125 spouting.

Limitations of the use of this building product

1. The product cannot be installed onto fascia or cladding with incompatible materials, and cannot run off onto incompatible materials. Material compatibility, contact and run-off are to be adhered to in accordance with E2/AS1 Tables 20, 21 and 22.

2. Site locations must be evaluated in areas with high wind and/or salt and/or thermal or industrial atmospheric conditions. These locations may require specific engineering design (SED). Designers must consult the metal supplier's information for specific durability requirements (reference E2/AS1 Table 20).

Maintenance requirements

Refer to the care and maintenance document listed under supporting documentation.

1. Inspect the product every 3 months to check for build-up of residue.
2. Wash the exterior surface of the product at a minimum of every 6 months, and immediately after inspection if required. Spray and rinse; scrub with a soft nylon brush if needed.

Relevant building code clauses

COMPLIANCE / REGULATION	DETAIL
E2/AS1 External moisture	Table 20
AS/NZS 2179.1:2014	Section 2.2.3
B2/AS1	Table 1: Durability requirements of nominated building element

Chief 125 aluminium internal spouting bracket contributes to compliance by —

> **E2/AS1 Table 20 — "Material selection"**
> The product is classified as "sheltered" and the material selection shown in Table 1 of this BPIR meets the requirements of Table 20 for exposure zones B, C, D and E for "aluminium" materials.

> **AS/NZS 2179.1:2014 Section 2.2.3 — aluminium alloys for rainwater accessories shall be of the 1000, 3000, 5000 or 6000 series complying with AS/NZS 1734, AS/NZS 1866 or AS/NZS 1867.**
> The bracket is manufactured from 5000 series aluminium, as shown in Table 1 of this BPIR.

> **B2/AS1 Table 1 — Durability requirements of nominated building element**
> External gutters are required to have a durability of 5 years. A 10-year warranty is provided with this product, provided the maintenance conditions are met.

Supporting documentation

The following additional documentation supports the above statements.

DOCUMENT NAME	WEBLINK
Chief 125mm brochure & specification	Chief Spouting Brochure and Specification.pdf
Maintenance document	National maintenance document.pdf
Material compatibility — selection	Continuous Group Material Compatibility Material Selection v1.pdf
Material compatibility — in contact	Continuous Group Material Compatibility — Compatibility of materials in contact v1.pdf
Material compatibility — subject to run-off	Continuous Group Material Compatibility — Compatibility of materials subject to run off v1.pdf
Warranty document	Continuous Group Warranties

Manufacturing and supply locations

TABLE 3 — CONTINUOUS GROUP MANUFACTURING AND/OR SUPPLY LOCATIONS

LOCATION	COMPANY DETAILS
Northland	Northland Continuous Spouting Ltd (NZBN 9429032689105) 2 Sammaree Place, Kerikeri — northland@continuous.co.nz
Auckland	Continuous Spouting Auckland Ltd (NZBN 9429034029862) 94 Takanini School Road, Takanini, Auckland — auckland@continuous.co.nz
Waikato	Continuous Waikato and Bay of Plenty Ltd (NZBN 9429030330535) 141 Queens Street, Leamington, Cambridge — waikato@continuous.co.nz
Bay of Plenty	Continuous Waikato and Bay of Plenty Ltd (NZBN 9429030330535) 31B Enterprise Drive, Papamoa, Tauranga — bop@continuous.co.nz
Gisborne	Streetwise Spouting Ltd (NZBN 9429042306276) 4 Leith Street, Gisborne — gisborne@continuous.co.nz
Hawke's Bay	Rooftech Hawke's Bay Ltd (NZBN 9429035443889) 2/7 Cadbury Road, Onekawa, Napier — hawkes_bay@continuous.co.nz
Taranaki	Gutter Solutions Ltd (NZBN 9429036739240) Unit 2, 20 Pacific Place, Gonville, Whanganui — taranaki@continuous.co.nz
Whanganui / Manawatu	Gutter Solutions Ltd (NZBN 9429036739240) Unit 2, 20 Pacific Place, Gonville, Whanganui — manawatu@continuous.co.nz
Wellington	Wellington Continuous Spouting Ltd (NZBN 9429043333974) Unit B, 1 Prosser Street, Porirua — wellington@continuous.co.nz
Nelson / Marlborough	Continuous Spouting South Ltd (NZBN 9429050107209) 7 Fuji Court, Stoke, Nelson — nelson@continuous.co.nz
Westland	Continuous Spouting South Ltd (NZBN 9429050107209) 51-57 Revel Street, Hokitika — westland@continuous.co.nz
Christchurch / North Canterbury	Continuous Spouting South Ltd (NZBN 9429050107209) 16 Westland Place, Izone Industrial Estate, Rolleston — canterbury@continuous.co.nz
Mid / South Canterbury	Continuous Spouting South Ltd (NZBN 9429050107209) 126 Dobson Street, Ashburton — canterbury@continuous.co.nz
Central Otago	Continuous Spouting South Ltd (NZBN 9429050107209) 7 Connelly Way, Cromwell — otago@continuous.co.nz
Coastal Otago	Continuous Spouting South Ltd (NZBN 9429050107209) 8 Benson Close, Mosgiel — otago@continuous.co.nz
Southland	Continuous Spouting South Ltd (NZBN 9429050107209) 72 Leet Street, Invercargill — southland@continuous.co.nz

Continuous Group are members of the NZ Metal Roofing Manufacturers Incorporated and the Roofing Association of New Zealand.