100MM ROUND · FS-100

100MM DOWNPIPE



FS-100

When the roof sheds more water. FS-100 carries 7,690mm² for larger residential and light commercial catchments, with spreader and branch fittings to move water where it needs to go.

Ideally suited for large residential roofs and light commercial buildings.

- 100mm round roll-formed downpipe
- 7,690mm² cross-section capacity
- Strap or clamp bracket options
- Brackets at up to 2400mm centres
- Colour matched to your spouting
- Up to 20 year material warranty

SPECIFY YOUR 100MM DOWNPIPE

FINISH RANGE	DOWNPIPE MATERIAL	COLOUR CHOICE	BRACKETS
CG Range	ColorCote MagnaFlow pre-painted G300 steel, min 200gsm	17 CG Colours	Strap or clamp
Designer Range	ColorCote MagnaFlow pre-painted G300 steel, min 200gsm or ColorSteel Maxam, min 150gsm	25 Designer Colours	Strap or clamp
Specialty Range	ColorCote MagnaFlow pre-painted G300 steel, min 200gsm or ColorSteel Maxam, min 150gsm	20 Specialty Colours	Strap or clamp
Copper	¾ hard pure copper, grade C12200	Natural patina	Strap or clamp

AVAILABLE FITTINGS

95° and 30° bends, spreader tees, branch tees, joiners, drain covers

CAPACITY

7,690mm² cross-section

For downpipe calculations by roof area, refer to MRM Code of Practice sections 5.4.1, 5.4.2 and 5.7.



100mm Downpipe



100mm Downpipe Strap



100mm Adjustable clamp



100mm 95° bend



100mm 30° bend



100mm Tee Junction

Additional components available.

AVAILABLE FROM THESE CONTINUOUS GROUP LOCATIONS

Northland	Auckland	Waikato	Bay of Plenty	Taranaki
Gisborne	Hawke's Bay	Manawatū	Kapiti Coast	Wairarapa
Wellington	Nelson	Marlborough	Buller	West Coast
Canterbury	Otago	Southland		

0800 50 1993
www.continuous.co.nz
cg@continuous.co.nz

All information, images and drawings are correct at time of publication August 2026