100 × 55MM RECTANGULAR · EF-100X55

100×55MM DOWNPIPE



EF-100X55

The rectangular Ezi-Flo. Extruded 6060-T5 aluminium, powder-coated and sealed — a flat profile that sits tight against the wall on charged lines and tank collection.

Ideally suited for tight wall lines and flat-face architecture, water collection and charged lines.

- 100 × 55mm rectangular extruded aluminium downpipe
- 5,500mm² cross-section capacity
- Sealed — suits tank collection & charged lines
- Brackets at up to 1800mm centres
- Powder-coated after extrusion — every colour available
- 15 year perforation warranty, zones B to E

SPECIFY YOUR 100×55MM DOWNPIPE

FINISH RANGE	DOWNPIPE MATERIAL	COLOUR CHOICE	BRACKETS
CG Range	6060-T5 extruded aluminium, powder-coated after extrusion	17 CG Colours	Back fix
Designer Range	6060-T5 extruded aluminium, powder-coated after extrusion	25 Designer Colours	Back fix
Specialty Range	6060-T5 extruded aluminium, powder-coated after extrusion	20 Specialty Colours	Back fix
Any colour	Because the finish is applied after extrusion, every listed colour is available	Powder-coat match	Back fix


AVAILABLE FITTINGS

95° and 30° bends, sideways bends, L spreaders, spreader tees, spreader end caps, branch tees, joiners

CAPACITY

5,500mm² cross-section


For downpipe calculations by roof area, refer to MRM Code of Practice sections 5.4.1, 5.4.2 and 5.7.




100×55mm Downpipe



100×55mm Back-fix bracket



100×55mm 95° bend



100×55mm Joiner

Additional components available.

0800 50 1993
www.continuous.co.nz
cg@continuous.co.nz

All information, images and drawings are correct at time of publication August 2026