
80MM ROUND · EF-80

80MM DOWNPIPE



EF-80

Extruded 6060-T5 aluminium, then powder-coated. EF-80 is sealed, so it can collect water into storage tanks and carry head pressure on a charged line.

Ideally suited for water collection, charged lines, runs inside the building envelope, and exposure zones B to E.

- 80mm round extruded aluminium downpipe
- 4,876mm² cross-section capacity
- Sealed — suits tank collection & charged lines
- Brackets at up to 1800mm centres
- Powder-coated after extrusion — every colour available
- 15 year perforation warranty, zones B to E

SPECIFY YOUR 80MM DOWNPIPE

FINISH RANGE	DOWNPIPE MATERIAL	COLOUR CHOICE	BRACKETS
CG Range	6060-T5 extruded aluminium, powder-coated after extrusion	17 CG Colours	Clamp
Designer Range	6060-T5 extruded aluminium, powder-coated after extrusion	25 Designer Colours	Clamp
Specialty Range	6060-T5 extruded aluminium, powder-coated after extrusion	20 Specialty Colours	Clamp
Any colour	Because the finish is applied after extrusion, every listed colour is available	Powder-coat match	Clamp

AVAILABLE FITTINGS

95° and 30° bends, spreader tees, spreader end caps, branch tees, joiners, drain covers

For downpipe calculations by roof area, refer to MRM Code of Practice sections 5.4.1, 5.4.2 and 5.7.



80mm Downpipe



80mm Adjustable clamp



80mm 95° bend



80mm 30° bend



80mm Tee Junction

Additional components available.

AVAILABLE FROM THESE CONTINUOUS GROUP LOCATIONS

Northland, Gisborne, Wellington, Canterbury, Auckland, Hawke's Bay, Nelson, Otago, Waikato, Manawatū, Marlborough, Southland, Bay of Plenty, Kapiti Coast, Buller, Taranaki, Wairarapa, West Coast

0800 50 1993
www.continuous.co.nz
cg@continuous.co.nz

All information, images and drawings are correct at time of publication August 2026