
140MM · TRUSS FASCIA

140 N-LINE



A 140mm ribbed steel truss fascia that fixes straight to the rafter ends — no timber, no painting, and a dead-straight line the length of the roof.

Ideally suited for new builds, and pairs with the full residential spouting range.

- 140mm ribbed truss fascia
- Soffit slope up to 30°
- Soaker or hand-cut mitre corners
- 15 year perforation warranty
- Bracket spacing up to 900mm
- Never needs painting

SPECIFY YOUR 140 N-LINE FASCIA

FINISH RANGE	FASCIA MATERIAL	COLOUR CHOICE	CORNER STYLING
CG Range	ColorCote MagnaFlow pre-painted G300 steel, min 200gsm	17 CG Colours	Soaker or hand-cut mitre
Designer Range	ColorCote MagnaFlow pre-painted G300 steel, min 200gsm or ColorSteel Maxam, min 150gsm	25 Designer Colours	Soaker or hand-cut mitre
Specialty Range	ColorCote MagnaFlow pre-painted G300 steel, min 200gsm, MagnaFlow Plus pre-painted G300 steel, min 200gsm* or ColorSteel Maxam, min 150gsm	20 Specialty Colours	Soaker or hand-cut mitre

* Limited colours available


COMPATIBLE SPOUTING

Chief · Big Chief · Quartz · Quartz Plus · Cube 125 · Halo 125 · Halo 150 · Archie Box*

FASCIA HEIGHT

140mm

*Archie Box limited to certain sizes. 140 N-Line is a regional profile — see availability below.



Fascia and truss bracket

The 140 N-Line panel clips onto a 0.95mm G300 steel truss bracket fixed to the rafter end, giving a 140mm face, an 18mm top return and a 37mm bottom hem that carries the soffit.

Brackets are spaced at up to 900mm and accommodate a soffit slope of up to 30°.

140 N-LINE IS AVAILABLE FROM THESE CONTINUOUS GROUP LOCATIONS


Northland
Auckland
Waikato
Bay of Plenty
Kapiti Coast
Wairarapa
Wellington

0800 50 1993
www.continuous.co.nz
cg@continuous.co.nz

All information, images and drawings are correct at time of publication August 2026

TECHNICAL SPECIFICATION

140 N-LINE 140mm Truss Fascia



DIMENSIONS & INSTALLATION

Fascia height	**140mm**
Series	**Truss Series**
Maximum bracket spacing	**900mm**
Maximum soffit slope	**30°**
Corner styling	**Soaker or hand-cut mitre**
Finish ranges	**CG, Designer, Specialty**

Compatible spouting: Chief, Big Chief, Quartz, Quartz Plus, Cube 125, Halo 125, Halo 150 and Archie Box (limited to certain sizes). Available in Northland, Auckland, Waikato, Bay of Plenty, Kapiti Coast, Wairarapa and Wellington.

PRODUCT SPECIFICATIONS

Pre-painted steel	0.55mm G300 — ColorCote MagnaFlow with min 200gsm alloy/zinc/magnesium coating, Colorcote MagnaFlow Plus with min 200gsm alloy/zinc/magnesium with PVDF coating or ColorSteel Maxam with min 150gsm alloy/zinc/magnesium coating
Truss bracket	0.95mm G300 steel with min 125gsm alloy/zinc/magnesium protective coating
Recommended fixings	Minimum Class 4 screw and/or rivet fasteners, compatible with substrate and bracket material. Stainless steel fixings and components are not compatible with our materials
Installation notes	Gable ends may require packing under the rafter. Install the bottom purlin after fascia installation. Soffit bearers are required on all hip corners. Metal fascia is a specialised system — DIY is not recommended, supported or approved; installation is available throughout New Zealand

SCOPE OF USE

Continuous Group fascia systems are intended to finish and protect the rafter ends at the perimeter of a building, to carry the spouting, and to close the soffit line. The fascia is positioned outside the building envelope.

NZBC COMPLIANCE

Test information from Pacific Coilcoaters and New Zealand Steel, combined with the past history of these products, indicates that provided use and maintenance follow current literature, Continuous Group systems can be expected to meet the performance criteria in clause E2 of the New Zealand Building Code.

DURABILITY

Pre-painted steel products are fit for purpose in environment zones B and C;* zone D may require a pre-approval warranty application based on the site address.*

*In all cases, areas with high wind and/or salt and/or thermal or industrial atmospheric conditions may require specific engineering design (SED). Reference: Section 4, "Durability", NZS 3604:2011.

MAINTENANCE

Regular maintenance ensures the useful life of the products. Minimum interval of every 6 months, or as often as needed to avoid build-up of dirt, salt and pollen on the fascia surface. Spray and rinse with water and, if necessary, scrub with a soft nylon brush. Specific products are listed in our Care & Maintenance document.

WARRANTY

MagnaFlow & Maxam pre-painted steel*

15 year Perforation warranty — exposure zones B, C and D.

10 year Paint warranty — exposure zones B, C and D.

*Subject to manual washing depending on exposure zone. Full details and conditions of our comprehensive Warranty are on our website.

0800 50 1993 · www.continuous.co.nz · cg@continuous.co.nz

All information, images and drawings are correct at time of publication August 2026